

Generating Rates		Prime	Standby
Power	kVA	250	275
Power	kW	200	220
Current	(cos Phi=0,8) A	360	396
Standard Voltage	V	400	400
Revolution Per Minute	r.p.m	1500	1500
Rated At Power Factor	Cos Phi	0,80	0,80

### Standard Features

- ✓ 4 stroke 1500RPM, water cooled heavy duty diesel engine
- ✓ Dry type replacable air filter
- ✓ Heat-resistant radiator for 50 °C
- ✓ Flexible oil pipes and oil draining valve
- ✓ Pre-heater
- ✓ Electronic type governor
- ✓ 4 poles synchrontype, single bearing, brushless alternator
- ✓ Batteries and cables
- ✓ Electrostatic paint coated, steel, welded chassis
- ✓ Fuel tank housed in the chassis
- ✓ Industrial type silencer
- ✓ Electronic battery charger
- ✓ Electrical wiring diagram
- ✓ User manual and operating manual
- ✓ Protection system and auto / manual mode
- ✓ Lubrication oil and anti – freeze

### Optional Equipments

- ✓ Soundproof canopy
- ✓ Automatic transfer switch
- ✓ Circuit Breaker
- ✓ Trailer
- ✓ External fuel tank
- ✓ Heating system for fuel tank
- ✓ Oil heater
- ✓ Fuel filling system (Automatic / Manual)
- ✓ Analog indicators
- ✓ 1 Phase - 3 phase switch plugs
- ✓ Alarm system for fuel level
- ✓ Remote control and monitoring

**Prime Power :** Supplying of electrical power at variable load for an unlimited number of hours in the event of normal utility powerfailure according to ISO8528-1. 10% over load capability is available.

**Stand By Power :** Supplying of electrical power at variable load, in the event of normal utility power failure according to ISO8528-1. This rating is maximum power, no overload capability is available.

### Engine Specifications

Brand		JOHN DEERE
Model		6068HFU55
Engine Power	(kWm / hp)	239
Revolution Per Min	(r.p.m)	1500
Total Displacement	(L)	6,8
Cylinders Orientation		6 Vertical Inline
Broke x Stroke	(mm x mm)	106x127
Compression Orientation		17,2
Governor Type		Electronic
Aspiration System		Turbo AAC
Injection		Direct Injection
Cooling		Water cooled
Electrical System	(VDC)	12 V
Lub-oil Capacity	(L)	TBA
Engine Coolant Capacity	(L)	34,8
Fuel Tank Capacity	(L)	400
Maximum Exhaust Temperature	(°C)	523
Maximum Exhaust Gas Flow	(m3/h)	2238
Maximum Allowed Back Pressure	(kPa)	7,5
Cooling Air Flow	(m3/min)	TBA
Fuel Consumption 50 %	(L/h)	27,4
Fuel Consumption 75 %	(L/h)	45,7
Fuel Consumption 100 %	(L/h)	53

- ✓ Replacable cylinder jacket
- ✓ Dry type replacable air filter
- ✓ Heat-resistant radiator for 50 °C

### Alternator Specifications

Standard Voltage	(V)	400
Frequency	(Hz)	50
Stationary Voltage Regulation	(±)	1
Short Circuit Current		300%
Insulation		H
Protection		IP23
Efficiency	(%)	92,2
Overloading		1 Hour - %110
Rated At Power Factor	(cos Phi)	0,80
Total Harmonic Distortion Rate		3
Connection Style		Star
Number of Pole		4
Number of Bearing		Single

- ✓ Self-cooled
- ✓ Electronic type automatic voltage regulator (AVR)
- ✓ 4 poles, self-excitation, brushless, synchrontype alternator

### Dimensions Without Canopy and Weight

WIDTH x LENGTH x HEIGHT	mm	1300x2980x1731
Wet Weight	kg	2102,51

### Dimensions With Canopy and Weight

WIDTH x LENGTH x HEIGHT	mm	2135x3645x2300
Wet Weight	kg	2592,51



### Control Panel Features

- ✔ Diesel and gas genset support
- ✔ 400Hz operation support
- ✔ 400 event logs full snapshot
- ✔ Multiple Automatic test program
- ✔ 3 level configuration password
- ✔ 128x64 graphical LCD display
- ✔ Downloadable language
- ✔ Waveform display of V&I
- ✔ Harmonic analysis of V&I
- ✔ Synchroscope & check synch
- ✔ 16 Amp MCB & GCB outputs
- ✔ 8 configurable digital outputs
- ✔ Outputs expandable to 40
- ✔ 4 configurable analog outputs
- ✔ Battery charge run enabled
- ✔ Weekly Operation Schedule
- ✔ Dual mutual standby with equal aging of gensets
- ✔ Manual speed fine adjust some ECU's
- ✔ Automatic fuel pumpcontrol
- ✔ Disable protection feature
- ✔ Excess protection power
- ✔ Reverse power protection
- ✔ Overload IDMT protection
- ✔ Load shedding, dummy load
- ✔ Multiple load management
- ✔ Waveform display of V&I
- ✔ Battery back-up real time clock
- ✔ Idle speed control
- ✔ All parameters front panel editable
- ✔ Multiple nominal conditions
- ✔ Contactor & MCB drive
- ✔ 4 quadrant genset power counters
- ✔ Mains power counters
- ✔ Fuel filling counter
- ✔ Fuel consumption counter
- ✔ Free configuration software
- ✔ Allow SMS controls
- ✔ Mobile genset support
- ✔ Automatic GSM geo-location
- ✔ GPS connectivity (USB & RS232)
- ✔ Modem & ethernet diagnostic
- ✔ Configurable through USB, RS-485, Ethernet and GPRS
- ✔ Ready for central monitoring Ethernet and GPRS